



An Improved Channel Estimation Approach for MIMO-OFDM Systems

Zhen Lu

A thesis submitted in fulfillment of requirements for the degree of
Master of Engineering (Research)

Centre for Real Time Information Technology
Faculty of Engineering and Information Technology
University of Technology, Sydney

Sydney, 2010

CERTIFICATE OF AUTHORSHIP/ORIGINALITY

I certify that the work in this thesis has not previously been submitted for a degree nor has it been submitted as part of requirements for a degree except as fully acknowledged within the text.

I also certify that the thesis has been written by me. Any help that I have received in my research work and the preparation of the thesis itself has been acknowledged. In addition, I certify that all information sources and literature used are indicated in the thesis.

Signature of Student

Zhen Lu

Acknowledgment

The thesis is by far the most significant achievement in my life, and I would like to thank the following people, without their support and help, I could not have completed the work.

Most of all, I would like to express my appreciation to my principal supervisor, Mr Anthony Kadi, for offering me such an vital opportunities to study at the University of Technology Sydney, for his patience, guidance and wisdom, which have accorded me numerous insights during my research.

I also sincerely thank my co-supervisor, Dr Tim Aubrey, for his support, experience and direction during the course of the project. His enthusiastic supervision of this project is gratefully acknowledged.

I want to thank all my friends and my colleagues in University of Technology Sydney. Their friendship made my research life enjoyable.

Last but by no means least, I would like to thank my parents for their continuous support and encouragement throughout the years, and I will be forever indebted to them for all that they have done.

Table of Contents

List of Figures.....	iv
List of Tables	vi
List of Abbreviations	vii
List of Mathematical Terms.....	ix
Abstract.....	x
1 Introduction	1
1.1 MIMO	1
1.2 Brief History of MIMO.....	2
1.3 Benefits of MIMO.....	3
1.4 OFDM Combined MIMO	3
1.5 Objectives.....	5
1.6 Main Contributions of the Thesis.....	5
1.7 Thesis Outline	6
2 Literature Review.....	7
2.1 MIMO-OFDM	7
2.2 Crucial Techniques of MIMO & OFDM	8
2.2.1 Transceiver Algorithms of MIMO	8
2.2.2 Channel Coding.....	11
2.2.3 Precoding	12
2.2.4 Antenna Selection	13
2.2.5 Adaptive Techniques.....	14
2.3 A Practical Issue in MIMO-OFDM: Channel Estimation.....	16
2.3.1 The Significance of Channel Estimation.....	16
2.3.2 Categories of Channel Estimation.....	16
2.3.3 Current Research of Channel Estimation in MIMO-OFDM.....	17
2.3.4 Problem of Current Channel Estimation in MIMO-OFDM.....	19
2.4 MIMO-OFDM and Wireless Standards.....	20
2.5 Justification of Work.....	21
3 Theory	23
3.1 Propagation Channel Model.....	23
3.1.1 Large Scale Path Loss Models	23

3.1.2	Small Scale Fading Models.....	24
3.1.3	Rayleigh Fading Channel Model	26
3.2	MIMO System Model.....	26
3.2.1	MIMO and Flat Fading Channel	27
3.2.2	MIMO and Frequency Selective Fading Channel.....	27
3.3	Space-Time Coding.....	28
3.3.1	How Space-time Coding Performs.....	28
3.3.2	Space-time Block Coding for Rayleigh Fading Channel.....	29
3.4	OFDM.....	32
3.4.1	OFDM in Broadband Wireless Networks	32
3.4.2	OFDM Generation	33
3.4.3	OFDM and MIMO	34
3.5	A MIMO-OFDM System Model	36
3.6	Channel Estimation.....	37
3.6.1	Pilots Schemes for Channel Estimation in MIMO-OFDM.....	38
3.6.2	Algorithms for MIMO-OFDM Systems	39
3.7	Conditional Model-order Estimation	42
4	A Hybrid CME-LS Channel Estimation Approach.....	45
4.1	Hybrid CME-LS Approach for SISO-OFDM Systems	47
4.2	CME-LS Based Approach for MIMO-OFDM Systems	50
5	Simulation and Results	53
5.1	Hybrid CME-LS in MIMO-OFDM Systems.....	53
5.1.1	Investigation of Different Pilot Schemes	53
5.1.2	CME-LS in Non-zero Taps Estimation.....	67
5.1.3	CME-LS performance with QPSK.....	68
5.1.4	Comparison of CME-LS and CME-MMSE.....	70
5.2	Comparison of CME-LS & MDL Approaches in MIMO-OFDM.....	71
5.2.1	MDL for MIMO-OFDM.....	71
5.2.2	Performance comparison in MIMO-OFDM	71
5.2.3	Computational Complexity Analysis between CME & MDL in MIMO-OFDM	77
5.3	Summary	80
6	Hybrid CME-LS Approach for Broadband WiMAX Based MIMO-OFDM Systems	82
6.1	CME-LS for Fixed Broadband MIMO-OFDM Systems	82
6.2	CME-LS for Mobile broadband MIMO-OFDMA System.....	85
6.3	Summary	93
7	Hardware Verification.....	94
7.1	An Overview of the Testbed.....	94
7.2	Software Development.....	96

7.3	Experimental Design.....	102
7.4	Experimental Results	105
8	Summary and Conclusion	109
8.1	Chapter Summary.....	109
8.2	Conclusions.....	111
8.3	Future Work	112
APPENDIX A: Publications.....		114
APPENDIX B: Matlab Codes		115
APPENDIX C: C Language Codes.....		117
APPENDIX D: Hardware Introduction		126
Bibliography		127

List of Figures

Figure 1.1 (a) MIMO (b) SISO communication system	2
Figure 1.2 Spectra of five carriers orthogonal to each other.....	4
Figure 1.3 A broadband channel divided into many parallel narrowband channels.....	4
Figure 2.1 (a) Schematic of the spatial multiplexing (b) Schematic of the Alamouti scheme.....	8
Figure 2.2 HBLAST encoder structure	9
Figure 2.3 space-time-frequency coding.....	11
Figure 2.4 Channel Coding	12
Figure 2.5 A general precoding with spatial multiplexing encoder	12
Figure 2.6 A general precoding with space-time coding encoder.....	12
Figure 2.7 Generic antenna selection in MIMO system	13
Figure 2.8 Operation of adaptive equaliser	14
Figure 2.9 Multipath wireless propagation	19
Figure 3.1 Category of small scale fading	25
Figure 3.2 Rayleigh fading envelop ($fd=100\text{Hz}$).....	26
Figure 3.3 General overview of a space-time encoder of a MIMO system	28
Figure 3.4 2×2 Alamouti scheme	30
Figure 3.5 Comparison of the BER performance between no diversity and Alamouti scheme for different modulation over Rayleigh flat fading channel.....	31
Figure 3.6 OFDM in broadband wireless networks.....	32
Figure 3.7 OFDM system block diagram.....	33
Figure 3.8 Block diagram of a MIMO-OFDM system	34
Figure 3.9 MIMO-OFDM system model.....	37
Figure 3.10 Pilot scheme I: Non-orthogonal Pilot pattern for MIMO with N_t transmit antennas.....	38
Figure 3.11 Pilot scheme II: Time -orthogonal Pilot pattern for MIMO with N_t transmit antennas.....	39
Figure 4.1 Problem of current channel estimation approaches in MIMO-OFDM.....	46
Figure 4.2 Significance of number of channel taps estimation.....	46
Figure 4.3 CME-LS channel estimation	48
Figure 4.4 SISO-OFDM.....	49
Figure 5.1 Flow chart of Matlab code for transmitter	54
Figure 5.2 Flow chart of Matlab code for receiver	55
Figure 5.3 Probability of correct detection for CME-LS with 8 pilots in 2×2 MIMO-OFDM system ($L=1, 2, 3$).....	56
Figure 5.4 Probability of correct detection ($L=4$)	57
Figure 5.5 Compare BER performances between the CME-LS and estimation with known number of taps.....	58
Figure 5.6 Probability of correct detection for CME-LS with 16 pilots in MIMO-OFDM	59
Figure 5.7 Pilot scheme II for 2×2 MIMO-OFDM.....	60
Figure 5.8 Probability of correct detection with different number of taps using scheme II (16 pilots) in MIMO-OFDM.....	60
Figure 5.9 Comparison of BER performances between CME-LS and LS with known L using scheme II (16 pilots) in MIMO-OFDM	63
Figure 5.10 Probability of correct detection for CME-LS with scheme II (8 pilots).....	64

Figure 5.11 Comparison of BER performances between CME-LS and LS with known L using scheme II (8 pilots).....	65
Figure 5.12 Performance comparison between the two pilot schemes	66
Figure 5.13 Probability of correct detection of CME-LS in the MIMO-OFDM system with other schemes	69
Figure 5.14 BER performance using other schemes	69
Figure 5.15 Comparison between CME-LS and CME-MMSE ($L=4$)	70
Figure 5.16 Comparison of Probability of correct detection between CME-LS & MDL-LS with 8 pilots in MIMO-OFDM system.....	72
Figure 5.17 Comparison of BER among LS with known L , CME-LS & MDL-LS with 8 pilots ($L=3$) in MIMO-OFDM system	73
Figure 5.18 Comparison of probability of correct detection between CME-LS and MDL-LS with 16 pilots in MIMO-OFDM	73
Figure 5.19 Comparison of BER performances among LS with known L , CME-LS and MDL-LS with 16 pilots in MIMO-OFDM	74
Figure 5.20 Problem of CME-LS and MDL-LS with scheme I (16 pilots)	75
Figure 5.21 Compare the probability of correct detection between CME-LS & MDL-LS with scheme II (16 pilots)	76
Figure 5.22 Complexity comparison (difference only) between CME & MDL.....	79
Figure 6.1 Probability of correct detection in fixed WiMAX IEEE802.16d using SUI-4 channel model	84
Figure 6.2 Comparison of BER performance for CME-LS and LS with known L in fixed WiMAX IEEE 802.16d using SUI-4 channel model.....	84
Figure 6.3 Comparison of WiMAX OFDM and OFDMA	85
Figure 6.4 OFDMA carrier arrangement in clusters and groups	86
Figure 6.5 CME-LS in WiMAX based mobile MIMO-OFDMA system (group with 16 pilots)	90
Figure 6.6 Probability of correct detection (24 pilots).....	91
Figure 6.7 CME-LS in WiMAX based mobile MIMO-OFDMA system (group with 24 pilots)	92
Figure 7.1 SignalWAVE block diagram.....	95
Figure 7.2 Block diagram of the major system components.....	96
Figure 7.3 2N point IFFT	97
Figure 7.4 Flow chart for transmitter	99
Figure 7.5 Flow chart for receiver.....	100
Figure 7.6 Comparison between the transmitter and receiver.....	101
Figure 7.7 TIMS-301 basic system	102
Figure 7.8 Block diagram of 2×2 MIMO-OFDM baseband system with two resolvable paths	103
Figure 7.9 Block diagram of 2×2 MIMO-OFDM baseband system with three resolvable paths	103
Figure 7.10 Screenshot of the results with 2 paths	105
Figure 7.11 Comparison of accuracy ($L=2$)	106
Figure 7.12 Comparison of BER performance ($L=2$)	106
Figure 7.13 Comparison of accuracy ($L=3$)	107
Figure 7.14 Comparison of BER performance ($L=3$)	107
Figure 8.1 The future DSP based MIMO wireless testbed	113

List of Tables

Table 2.1 The categories of adaptive equaliser	15
Table 3.1 Large Scale Propagation Models	24
Table 3.2 Small Scale Fading Models.....	25
Table 5.1 Recommended pilot schemes for different propagation environments	67
Table 5.2 CME-LS in non-zero taps detection in MIMO-OFDM system	67
Table 5.3 Number of flops for each real operation	77
Table 5.4 Number of flops for each complex operation	78
Table 6.1 OFDM symbol parameters.....	82
Table 6.2 SUI-4 Channel Model (omni direction antenna) [L=3]	83
Table 6.3 OFDMA symbol parameters	87
Table 6.4 “Vehicular A” channel environment.....	88
Table 6.5 Estimated number of paths, $f_d = 40\text{Hz}$	88
Table 6.6 Estimated number of paths, $f_d=311\text{Hz}$	89
Table 7.1 Approximate delay values for cables	103
Table 7.2 Parameters for experiments.....	105

List of Abbreviations

ADC (A/D)	Analog to digital converter
ADSL	Asymmetric digital subscriber line
AIC	Akaike Information Criterion
ANSI	American National Standards Institute
AWGN	Additive white Gaussian noise
BER	Bit-error rate
BLAST	Bell Laboratories space-time
bps	Bits per second
BPSK	Binary phase-shift keying
BWA	Broadband wireless access
CC	Convolutional coding
CME	Conditional Model order Estimation
CP	Cyclic prefix
CSI	Channel state information
CSIT	Transmitter channel state information
DAC (D/A)	Digital to analog converter
dB	Decibels
DFE	Decision feedback equalisation
DFT	Discrete Fourier Transform
DMT	Discrete multi-tone systems
DSL	Digital subscriber line
DSP	Digital Signal Processing
ETSI	European Telecommunication Standard Institute
FDE	Frequency domain equalisation
FEC	Forward error control
FER	Frame-error rate
FFT	Fast Fourier Transform
flops	floating-point operations
FPE	Final Prediction Error
FPGA	Field Programmable Gate Array
GSM	Global system for mobile communications, a second-generation mobile communication standard
HDSL	High-bit-rate Digital Subscriber Line
IEEE	Institute of Electrical and Electronic Engineering
IDFT	Inverse Discrete Fourier Transform
IFFT	Inverse Fast Fourier Transform
ISI	Intersymbol interference
LMS	Least mean-squares
LOS	line-of-sight
LS	Least Squares
LST	Layered space-time code
MDL	Minimum Description Length
MIMO	Multiple-input multiple-output

MISO	Multiple-input single-output
ML	Maximum likelihood
MLSE	Maximum likelihood sequence estimation
MMSE	Minimum mean-square error
MRC	Maximum radio combine
MU	Multi-user
NLOS	non-line-of-sight
OFDM	Orthogonal frequency division multiplexing
OFDMA	Orthogonal frequency division multiple access
OSTBC	Orthogonal space-time block codes
PDA	Probabilistic Data Association
PDF	Probability Density Function
PER	Packet error rate
PMPR	Peak to mean power ratio
PRBS	Pseudo Random Binary Sequence
QAM	Quadrature amplitude modulation
QPSK	Quadrature phase-shift keying
QSTBC	Quasi-orthogonal STBC
RF	Radio frequency
RLS	Recursive least squares
RMS	Root mean square
RS	Reed-Solomon
SC	Single carrier
SER	Symbol to error rate
SIMO	Single-input multiple-output
SISO	Single-input single-output
SNR	Signal-to-noise ratio
SM	Spatial multiplexing
ST	Space-time
STBC	Space-time block code
STC	Space-time coding/space-time code
STTC	Space-time trellis code
SU	Single user
SUI	Stanford University Interim
3GPP	The third Group Partnership project
UMTS	Universal mobile telecommunications system
V-BLAST	Vertical BLAST
VDSL	Very-high-rate Digital Subscriber Line
WCDMA	Wideband code division multiple access
WiMAX	Worldwide Interoperability for Microwave Access, IEEE 802.16 standard
Wi-Fi	Wireless fidelity
WLAN	Wireless local area network
ZF	Zero Forcing

List of Mathematical Terms

f_c	carrier frequency
f_d	Doppler frequency
Δf	spacing between subcarriers
\mathbf{F}	FFT matrix
F_s	OFDM sampling frequency
G	guard interval
h	channel impulse response
\mathbf{H}	channel frequency response
\mathbf{I}	identity matrix
l_p	pilot position
K	number of subcarriers
L	number of multi channel paths (number of arrival, tap length)
\hat{l}	the estimated number of channel paths
N_t	number of transmit antennas
N_r	number of receive antennas
P	number of pilot symbols
s	transmitted space-time coded OFDM sequences
T_b	Useful Symbol Time
T_g	CP Time
T_s	time duration of one OFDM symbol
v	vehicle speed
y	received OFDM sequences
σ^2	noise variance
ε	transmitted power per symbol
τ	delay
\mathbf{w}	AWGN in time domain
Γ	gamma, $\Gamma(n+1)=n!$
Λ	diagonal matrix
$\mathbf{D}(x)$	diagonal matrix with x in its diagonal
$[\]^H$	Hermitian transpose
$[\]^T$	transpose of a matrix

Abstract

In wireless environments, signals bounce off many obstacles such as mountains, buildings, trees, etc. as they propagate between transmitters and receivers. The resultant signal at the receive antenna is, therefore, often the sum of the attenuated transmitted signal and one or more delayed versions of the transmitted signal. The received signal also suffers from intersymbol interference which degrades the quality of signal to a certain extent.

However, MIMO-OFDM systems are designed to take advantage of the multi-path properties in wireless communications and are capable of improving transmission rate, range and reliability simultaneously. MIMO-OFDM attracts a good deal of research and commercial interest because of the perceived benefits, and has been adopted in many wireless standards such as IEEE 802.11n, IEEE 802.16e. Such systems are also potential candidates for fourth-generation (4G) systems. However, practical problems still exist in implementing MIMO-OFDM, for example, in the estimation of channel state information (CSI). This thesis studies the issues of MIMO, OFDM and the relevant techniques of MIMO-OFDM, and focuses on proposing a practical, low complexity and accurate channel estimation method for such systems.

In a MIMO-OFDM system, CSI is required at the receiver to perform space-time decoding or diversity combining. In many practical wireless applications, the propagation environment is both complex and time-variant, leading to CSI estimation errors and overall system performance degradation. A variety of channel estimation approaches have been proposed in the literature to address this problem. One of the most important parameters of CSI is the number of significant or dominant propagation paths, also referred to as the number of channel taps. However, in most existing estimation schemes for MIMO-OFDM, there is an assumption that the number of channel taps is known at the receiver. In reality, in order to perform space-time decoding, the receiver needs to estimate the number of channel taps from the received signal with this estimation process sometimes aided by the insertion of pilot tones into the transmitted signal.

In this thesis, a pilot-assisted, conditional model-order estimation (CME) based channel estimation algorithm is presented. The approach can be utilised to detect both the number of channel resolvable paths and channel gains for MIMO-OFDM systems. The performance of the proposed algorithm is compared with the commonly used minimum description length (MDL) algorithm by mean of simulation in the context of a 2×2 MIMO-OFDM system. Results indicate that the new algorithm is superior to the MDL algorithm in channel order estimation over an unknown, noisy, multipath fading channel with limited pilot assistance. Furthermore, the proposed scheme is tested in both fixed and mobile broadband MIMO-OFDM systems based on WiMAX techniques in Matlab simulation, and its capacity is verified again for those near practical broadband MIMO-OFDM systems in the absence of prior knowledge of model parameters.

Finally, with the purpose to “make the thing work in practice”, a 2×2 MIMO baseband platform is built in order to demonstrate the proposed scheme. The platform consists of two DSP based, real-time development boards called SignalWAVE, produced by Lyrtech. Given the existing hardware components, the whole platform is built based on a fixed MIMO-OFDM system according to WiMAX standard, and the results demonstrate that the proposed algorithm is a valid approach in practice.